








solves gluing-problems








HAND APPLICATORS

	AES p/n	Description
	TR500 TR501 TR502	Glue stick handgun accepts 11-12 mm hot melt glue sticks Delivery of glue is with a mechanical trigger to apply dots/ lines with various nozzle sizes available Heating capacity: TR500,TR501 approx. 125 W Heating capacity: TR502 approx 500W at cold start then 40W at 205°C TR500- Electronic control, adjustable 100 to 205°C, overtemp protection, LED for power and heating TR501- Electronic control, fixed at 205°C , overtemp protection, LED for power and heating TR502- Thermostat control, fixed at 205°C
	MS200	Hand gun with a 250ml tank capacity to accept bulk type hot melt granulate, small pillows and 43mm sticks Delivery of glue is with a mechanical trigger to apply dots/ lines with various nozzle types and sizes available Heating capacity: 600 W with a 5 minute heat up Temperature control with an adjustable thermostat Temperature range: 20-200°C REPLACES THE MS150
	TR50.4	Hand gun to accept bulk type hot melt granulate, pillows, pellets and Ø42mm slug with a 200ml tank capacity Pneumatic pressure for delivery of glue to apply dots/ lines Heating capacity: 400 W Temperature control: adjustable thermostat Temperature range: 20-200°C
	TR55LCD	Hand gun to accept bulk type hot melt granulate, pillows, pellets and Ø42mm slug with a 330ml tank capacity Pneumatic pressure for delivery of glue to apply dots/ lines Heating capacity: 400 W Temperature control: adjustable electronic, LCD display Temperature range: 50-210°C
	TR60LCD	Hand gun to accept bulk type hot melt granulate, pillows, pellets and Ø42mm slug with a 250ml tank capacity pneumatic pressure for delivery of glue in a spray application (convertible to dots/ lines if required). Heating capacity: 400 W, 50-210°C Temperature control: adjustable electronic, LCD display Includes a Stand with a pressure regulator and manometer for glue delivery and another pressure regulator and manometer to control the spray air
	PH5563	Preheater - 4 litre tank capacity Heating capacity: 400 W Max. temperature: 150 degrees Temperature control: adjustable thermostat Temperature range: 0-150 degrees



solves gluing-problems

HAND APPLICATORS

	AES p/n	Description
	TR70LCD	Accepts a 310ml Al-cartridges: , pneumatic pressure for delivery of glue to apply dots/ lines . Heating capacity: 400 W Temperature control: adjustable electronic, 50-210°C
	TR80LCD	Accepts a 310ml Al-cartridges: , pneumatic pressure for delivery of glue in a spray application. (convertible to dots/ lines if required). Heating capacity: 400 W, 50-210°C Temperature control: adjustable electronic, LCD display Includes a Stand with a pressure regulator and manometer for glue delivery and another pressure regulator and manometer to control the spray air
	CH5398	Cartridge Preheater Accepts 2 x standard 310ml aluminium cartridges Cartridge size: , Ø47mm x 215mm length Heating capacity: 500W from cold start, 40W at 125°C Factory set temperature at approx. 125 degrees fixed.
	BL3544	Balancer Counterbalances the weight of your glue gun for ergonomic and safe usage. Load Capacity 1 to 2kg Cord length 1.6 m Solid aluminium construction Variable weight balancing with adjusting knob
	SS3587	Stand for Storing Includes 1 x Regulator for Precise adjustment of the air pressure from 0.15 -7 bar and 1x Manometer s for verifying the adjusted air pressure Provides ergonomic and safe storage of the glue gun Use with TR50.4, TR55LCD, TR70LCD
	SE3618	Stationary Equipment Post Post kit to mount handgun on stand 3587 for hands free application of glue when used in combination with foot switch FS3518. Ideal for gluing small parts and potting applications Stand SS3587 not included
	FS3518	Foot Switch Use your foot to dispense glue from the handgun. Combine with SE3618 above for hands free application