

5 43mm (1¾") tec glue gun

tec3150



High output 43mm (1¾") glue gun for industrial use. All-electric & extremely robust. Power-on light and removable integral stand with built in nozzle spanner.

Melt rate	3kg (6½ lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	300W
Heater	Cartridge
Temp Control	Interchangeable thermostat (see page 10)
Hot melt gun °C (°F)	195°C (380°F)
Low melt gun °C (°F)	130°C (260°F)
Power cable	3M (10ft)
Weight	1.15kg (2½lb)
Packaging	Plain box (5 per ctn)

tec6100



Extremely robust 43mm (1¾") pneumatic glue gun for industrial use. Reduces' operator fatigue, power-on light, 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	4.1kg (9lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	500W
Heater	Cartridge
Temp Control	Interchangeable thermostat (see page 10)
Hot melt gun °C (°F)	195°C (385°F) High temp polyamide version 215°C (420°F) also available
Low melt gun °C (°F)	130°C (265°F)
Power cable	3M (10ft)
Weight	1.4kg (3lbs)
Packaging	Plain box (5 per ctn)

tec3200



High output all-electric 43mm (1¾") glue gun for Industrial use. Extremely robust with electronic temperature control, automatic standby, plug-in temperature modules & power-on light.

Melt rate	3.5kg (8lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	400W
Heater	Cartridge
Temp Control	Electronic plug in temperature modules
Hot melt gun °C (°F)	195°C (380°F) fitted, 130°C (260°F) and 215°C (420°F) Plug-in modules included
Low melt gun °C (°F)	Covered above
Power cable	3M (10ft)
Weight	1.15kg (2½lb)
Packaging	Plain box (5 per ctn)

tec7100



Extremely robust, very high output 43mm (1¾") pneumatic glue gun for industrial use. Reduces' operator fatigue, speed loader to reduce down time and power-on light. 8 bar (120psi) 14 l/min (0.5 cfm) air supply required.

Melt rate	5.0 kg (11lb)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	1000W
Heater	Cartridge
Temp Control	Interchangeable thermostat (see page 10)
Hot melt gun °C (°F)	195°C (385°F) High temp polyamide version 215°C (420°F) also available
Low melt gun °C (°F)	130°C (265°F)
Power cable	3M (10ft)
Weight	2.3kg (5lb)
Packaging	Plain box (5 per ctn)



Not sure which glue?

Call us now for more information

See back for details



Adhesive test packs
available. Call now!

See back for details

Test Packs!



Formulation	Description	Colour	Open time	Viscosity
14	High delivery, very fast setting packaging adhesive	Light brown	Short	Low
1942	Product assembly adhesive for wood and many plastics, nylon, ABS & rigid PVC	Brown	Medium/Long	Medium
1X	Low viscosity, wood working and packaging adhesive. Medium open time	Light brown	Medium	Low
213	Economical, general purpose adhesive. Suitable for ceramics, rigid PVC & polystyrene	Light brown	Long	Medium
214	Economical, fast setting, packaging adhesive	Light brown	Short	Medium
23	Medium viscosity multi-purpose adhesive. For fabric, hard & soft wood, & many plastics	Light brown	Long	Medium
232	Economical, high viscosity, clear general purpose adhesive. Suitable for glass, fabrics, wood, card, and some plastics	Clear	Medium	High
240	High delivery, long open time, multi-purpose, clear adhesive. For use with many plastics & light gauge metals	Clear	Long	Medium
248	Very high performance, acrylic based hotmelt. Excellent adhesion to smooth and shiny surfaces	Clear	Long	Medium
260	High performance, long open time, tough, flexible adhesive. Suitable for ceramics, plastics & woods	Light brown	Long	Low
261	Economical, high performance, tough, flexible adhesive with long open time. For use with ceramics, plastics & woods	Light brown	Long	Low
265	Long open time product assembly adhesive for smooth and shiny surfaces, & many plastics	Light brown	Medium	Medium
267	High & low heat resistant, medium open time, product assembly adhesive for polypropylene, wood & metals	Light brown	Long	Low
342	High viscosity, fast setting, white adhesive with instant grab. Suitable for heavy duty carton board & cable attachment	White	Short	High
5	High delivery, low viscosity, long open time, product assembly adhesive for wood, plastic & metals	Light brown	Medium/Long	Low
LM44	Lowmelt, fast setting, high performance, white adhesive. Ideal for expanded polystyrene, thin films & balloons	White	Short	Low
Polyamide adhesive				
7784	High & low temperature-resistant multi-purpose polyamide adhesive	Amber	Medium	Medium
7785	High temperature-and chemical-resistant multi-purpose polyamide adhesive	Amber	Medium	Medium