
## 43mm (1¾") spraytec glue gun





Melt rate	4.2kg (10lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	500W
Heater	Cartridge
Temp Control	Interchangeable thermostat (see page 10)
Hot melt gun °C (°F)	180°C (350°F)
Low melt gun °C (°F)	n/a
Power cable	3M (10ft)
Weight	1.4kg (3lbs)
Packaging	Plain box (5 per ctn)



## **spraytec**<sup>™</sup> high performance 43mm (1¾") adhesive cartridges

Specially designed for use in the **tec6300** & **tec7300**, and available to bond virtually any material. The range provides variations in setting time, colour, heat resistance and viscosity to suit every application.

Formulation	Description	Colour	Open time	Viscosity
spraytec 410	Pallet stabilisation spray adhesive, also for expanded polystyrene	Light brown	Long	Medium
spraytec 420	General purpose spray adhesive. Suitable for fabric, upholstery foams, bubble film etc	Light brown	Up to 3 mins	Medium
spraytec 425	High delivery, high performance, spray adhesive for wood, many plastics, pre-cast concrete moulds	Light brown	Up to 3 mins	Low
spraytec 430	High performance, long open time spray adhesive. Suitable for polypropylene, foams, wood and cardboard	Light brown	Up to 6 mins	Medium



Extremely robust, 43mm (1¾") spray glue gun. Non-toxic adhesive spray system, sprays hotmelt at any angle, adjustable spray pattern to cover large areas. Apply hotmelt to heat sensitive substrates without damage. Speed loader to reduce downtime, plus power-on light. 8 bar (120psi) 85 l/min (3 cfm) air supply required.

Melt rate	5.25kg (11½lbs)/hr
Glue size	43mm (1¾") glue cartridge
Voltage	120V and 230V
Wattage	1000W
Heater	Cartridge
Temp Control	Interchangeable thermostat (see page 10)
Hot melt gun °C (°F)	180°C (350°F)
Low melt gun °C (°F)	n/a
Power cable	3M (10ft)
Weight	2.3kg (5lb)
Packaging	Plain box (5 per ctn)

